

IB1003	
Inductive proximity sensor	
Metal thread M12 x 1.0	
Cable	
Size 48mm	
Sensing range 2mm[f]	
Flush	
Electric design	DC 3 Wire
Output	NPN NO
Operating voltage [V]	10...36 DC
Current loading [mA]	100
Short-circuit protection	Yes
Reverse polarity protection	Yes
Overload protection	Yes
Voltage drop [V]	<3
Consumed current[mA]	<10
Real sensing range [mm]	2±10%
Operating range [mm]	0...1.6
Switch-point drift [%/Sr]	-10...10
Hysteresis [%/Sr]	3...20
Switching frequency [Hz]	700
Adjustment factors	Low carbon steel=1 /Stainless steel approx 0.7 /Brass approx 0.5 / Alumium approx 0.4 / Copper approx 0.3
Operating temperature [°C]	-25...75
Ambient humidity	35...95
Protection classification	IP67

Dimension		
Housing material	Stainless steel , Sensing face: PBT	
Switching state display LED	Red (90°)	
Connection	PVC-Cable /2m;3x0.14mm ²	
Wiring		
Core color		
BN +		
BU -		
BK Signal Line		
Accessory(Included)	Two fixed nuts	
	伊玛精密电子(苏州)有限公司	website: www.ema-electronic.com
	ema electronics	e-mail: enquiry@ema-electronic.com