

IB1017	
Inductive proximity sensor	
Metal thread M12 x 1.0	
Cable	
Size 48mm	
Sensing range 2mm[f]	
Flush	CE RoHS

Electric design	DC 2 Wire
Output	NO
Operating voltage [V]	10...36 DC
Current loading [mA]	100
Short-circuit protection	Yes
Reverse polarity protection	Yes
Overload protection	Yes
Voltage drop [V]	<4
Consumed current[mA]	<0.6
Real sensing range [mm]	2±10%
Operating range [mm]	0...1.6
Switch-point drift [%/Sr]	-10...10
Hysteresis [%/Sr]	3...20
Switching frequency [Hz]	700
Adjustment factors	el=1 /Stainless steel approx 0.7 /Brass approx 0.5 / Alumium approx 0.4 / Co
Operating temperature [°C]	-25...75
Ambient humidity	35...95
Protection classification	IP67

Dimension	
-----------	--

Housing material	Stainless steel , Sensing face: PBT
------------------	-------------------------------------

Switching state display LED	Red (90°)
-----------------------------	-----------

Connection	PVC-Cable /2m;3x0.14mm2
------------	-------------------------

Wiring	
Core color	
BN +	
BU -	
BK Signal Line	

Accessory(Included)	Two fixed nuts
---------------------	----------------