

Short-body

Ultra Short Housing

Proximity



Appearance		
Mounting	Shielded	
Housing size	φ 6.5	φ 6.5Y
Sensing distance	1mm/2mm ± 10%	
Housing material	Stainless steel	
Operating voltage	10~30V DC(Ripple < 10%)	
Voltage drop	< 1.5V	
Load Current , Max	150mA	
Current consumption	< 10mA	
Leakage current	< 0.01mA	
Switch frequency	2KHz	
Repeat accuracy	< 1.0%(Sr)	
Hysteresis	< 15%(Sr)	
Sensing surface material	PBT	
Operating Temperature	-25°C~+75°C	
Protective circuit	Short circuit	
Degree of protection	IP67	
Model No.	TSSF6.5-01 / TSSF6.5-02	TSSF6.5Y-01 / TSSF6.5-02
	:NPN Normally open :NPN Normally closed	:PNP Normally open :PNP Normally closed



Appearance		
Mounting	Shielded	
Housing size	M8	M12
Sensing distance	1mm/2mm ± 10%	2mm/4mm ± 10%
Housing material	Stainless steel	
Operating voltage	10~30V DC(Ripple < 10%)	
Voltage drop	< 1.5V	
Load Current , Max	150mA	
Current consumption	< 10mA	
Leakage current	< 0.01mA	
Switch frequency	2KHz	
Repeat accuracy	< 1.0%(Sr)	
Hysteresis	< 15%(Sr)	
Sensing surface material	PBT	
Operating Temperature	-25°C~+75°C	
Protective circuit	Short circuit, except TSSF08-02	
Degree of protection	IP67	
Model No.	TSSF08-01 / TSSF08-02	TSSF12-02 / TSSF12-04
	:NPN Normally open :NPN Normally closed	:PNP Normally open :PNP Normally closed

(HOT)

- Fiber Optic
- Slot Sensors
- Photoelectric
- Laser
- Proximity**
- Displacement
- Magnetic
- Contact
- Area
- Ultrasonic
- Vision
- Vibration
- Temperature
- Annexes

Guidance

- Inductive sensors**
- Standard distance
- Extended distance
- Long distance
- Square
- Mini square
- Mini-cylindrical
- Short-body**
- Ring-type
- Metal face
- Temperature
- Analog output
- DC 2 wires
- IP69K high protection

- Capacitive sensors**
- Cylindrical
- Correction resistanc type
- Flat type
- Level detection



Appearance

Mounting	Shielded				
Housing size	M8	M12	M18	M30	
Sensing distance	1mm/2mm ± 10%	2mm/4mm ± 10%	5mm/8mm ± 10%	10mm/16mm ± 10%	
Housing material	Stainless steel				
Operating voltage	10~30V DC(Ripple < 10%)				
Voltage drop	< 1.5V				
Load Current, Max	150mA				
Current consumption	< 10mA				
Leakage current	< 0.01mA				
Switch frequency	2KHz	2KHz/1Hz	1KHz/500Hz	300Hz/150Hz	
Repeat accuracy	< 1.0%(Sr)				
Hysteresis	< 15%(Sr)				
Sensing surface material	PBT				
Operating Temperature	-25°C~+75°C				
Protective circuit	Short circuit				
Degree of protection	IP67				
Model No.	NPN Normally open	TSF08-01NO/TSF08-02NO	TSF12-02NO/TSF12-04NO	TSF18-05NO/TSF18-08NO	TSF30-10NO/TSF30-16NO
	Others	NO:NPN Normally open	NC:NPN Normally closed	PO:PNP Normally open	PC:PNP Normally closed



Appearance

Mounting	Unshielded				
Housing size	M8	M12	M18	M30	
Sensing distance	2mm/4mm ± 10%	4mm/8mm ± 10%	8mm/16mm ± 10%	15mm/25mm ± 10%	
Housing material	Stainless steel	Nickle plated brass			
Operating voltage	10~30V DC(Ripple < 10%)				
Voltage drop	< 1.5V				
Load Current, Max	150mA				
Current consumption	< 10mA	< 20mA			
Leakage current	< 0.01mA				
Switch frequency	2KHz/1KHz	1KHz/500Hz	500Hz/150Hz	150Hz/100Hz	
Repeat accuracy	< 1.0%(Sr)				
Hysteresis	< 15%(Sr)				
Sensing surface material	PBT				
Operating Temperature	-25°C~+75°C				
Protective circuit	Short circuit				
Degree of protection	IP67				
Model No.	NPN Normally open	TSN08-02NO/TSN08-04NO	TSN12-04NO/TSN12-08NO	TSN18-08NO/TSN18-16NO	TSN30-15NO/TSN30-25NO
	Others	NO:NPN Normally open	NC:NPN Normally closed	PO:PNP Normally open	PC:PNP Normally closed

- Fiber Optic
- Slot Sensors
- Photoelectric
- Laser
- Proximity**
- Displacement
- Magnetic
- Contact
- Area
- Ultrasonic
- Vision
- Vibration
- Temperature
- Annexes

Guidance

- Inductive sensors**
- Standard distance
- Extended distance
- Long distance
- Square
- Mini square
- Mini-cylindrical
- Short-body**
- Ring-type
- Metal face
- Temperature
- Analog output
- DC 2 wires
- IP69K high protection


- Capacitive sensors**
- Cylindrical
- Correction resistanc type
- Flat type
- Level detection

Short-body

Extra Shot Outer Casing-Dimensions (Unit:mm)


M6.5

TSSF6.5-01/02/03 □ □




M6.5Y

TSSF6.5Y-01/02/03 □ □




M8

TSSF08-01/02/03 □ □



M12


TSSF12-02/04/06 □ □




General-Dimensions (Unit:mm)

M8

TSF08-01/02 □ □




TSN08-02/04 □ □




M12

TSF12-02/04 □ □




TSN12-04/08 □ □




M18

TSF18-05/08 □ □




TSN18-08/16 □ □




M30

TSF30-10/16 □ □



TSN30-15/25 □ □



Fiber Optic
Slot Sensors
Photoelectric
Laser
Proximity
Displacement
Magnetic
Contact
Area
Ultrasonic
Vision
Vibration
Temperature
Annexes
Guidance
Inductive sensors
Standard distance
Extended distance
Long distance
Square
Mini square
Mini-cylindrical
Short-body
Ring-type
Metal face
Temperature
Analog output
DC 2 wires
IP69K high protection
Capacitive sensors
Cylindrical
Correction resistanc type
Flat type
Level detection