





<p>ID1026</p> <p>Inductive proximity sensor</p> <p>Metal thread M30 x 1.5</p> <p>Cable</p> <p>Size 49 mm</p> <p>Sensing range 10mm[F]</p> <p>Flush</p>	
Electric design	AC/DC 2 Wire
Output	NC 
Operating voltage [V]	20...250 AC/DC
Current loading [mA]	250
Short-circuit protection	No
Overload protection	No
Voltage drop [V]	< 7.5 AC / 6 DC
Leakage current [mA]	<2(250V AC)<1.5(110V AC)<0.6(24V DC)
Real Sensing range [mm]	10±10%
Operating range [mm]	0...8
Switch-point drift [%/Sr]	-10...10
Hysteresis [%/Sr]	1...15
Switching frequency [Hz]	25AC/60DC
ESD [KV]	6KV III
EFT [KV]	2KV III
Walkie talkie experiment [mm]	<1
Adjustment factors	Low carbon steel=1 /Stainless steel approx 0.7 /Brass approx 0.4 / Aluminum approx 0.3 / Copper approx 0.2
Operating temperature [°C]	-25°C...80°C
Protection classification	IP67
Dimension	
Housing material	Stainless steel , Sensing face: PBT
Switching state display LED	Red (90°)
Connection	PVC Cable /2m; 2x0.34mm ²
Wiring	
Core color:	
BN +	
BU -	
	Using small-sized fuse ≤2A (fastly use) as indicated in the picture.
Accessory (Included)	Two fixed nuts