

Analog Output

Pre-wired




	Shielded			Unshielded		
Mounting	M12	M18	M30	M12	M18	M30
Size						
Sensing distance	0.1~3mm ± 10%	1~4mm ± 10%	5~10mm ± 10%	0.1~4mm ± 10%	1~7mm ± 10%	7~14mm ± 10%
Housing material				Nickel copper alloy		
Operating voltage			18~30V DC(Ripple < 10%)			
Fiber Optic			< 15mA			
Slot Sensors	Linear		< 5%			
Photoelectric	Switch frequency		100Hz			
Laser	Repeat accuracy		0.02mm			
Proximity	Current output	4~20mA/≤200Ω	0~20mA/≤200Ω	4~20mA/≤400Ω	0~20mA/≤200Ω	
	Voltage output			0~10VDC/≥4.7KΩ		
Displacement	Output type			PNP-Analog		
Magnetic	Sensing surface material			PBT		
Contact	Ambient temperature			-25°C~+75°C		
Area	Circuit protection			Reverse polarity		
Ultrasonic	Degree of protection			IP67		
Vision	Model No.	TAF12-03PA	TAF18-04PA	TAF30-10PA	TAN12-04PA	TAN18-07PA
		TAF12-03PV	TAF18-04PV	TAF30-10PV	TAN12-04PV	TAN18-07PV
						TAN30-14PA


Dimensions (Unit:mm)

M12

TAF12-03□□




TAN12-04□□




M18

TAF18-04□□




TAN18-07□□



M30

TAF30-10□□



TAN30-14□□

