

STS1921-0225

19-inch LCD

Open-Frame Touchscreen



Specifications	
Model	STS1921-0225
Color	Black
Active Display Area	14.8" x 11.85" / 376.32mm x 301.06mm
Diagonal	19"
Aspect Ratio	5:4
Native Resolution	1280 x 1024 at 60 Hz
Other Supported Resolutions	640x480 at 60Hz; 720x400 at 70Hz; 800x500 at 60Hz; 800x600 at 56, 60Hz; 1024x768 at 60Hz; 1280 x 800 at 60Hz
Number of Colors	16.7 million
Number of Touches	10-touch
Brightness (typical)	TouchPro PCAP: 225 nits
Response (typical)	5 msec
Viewing Angle	Horizontal: 85°/170°; Vertical: 80°/160°
Contrast Ratio	1000:1
On-Screen Display	Accessible through switches on the unit's tethered OSD Control box. Controls: Menu, Up, Down, Select, Power Settings: Brightness, Contrast, Clock, Phase, H-position, V-position, Auto-Adjust, Aspect Ratio, Sharpness, Color, Temperature, OSD Timeout, OSD Language, OSD H-Position, OSD V-Position, Recall Defaults, Video Priority, Information, Touch On Sleep Mode, Touch Through Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese Lockouts: OSD, Power
Video	HDMI V1.3 Type A receptacle for HDMI input Analog VGA on Female DB-15 connector DisplayPort V1.1a - Supports later versions of Display Port video input Input Video Horizontal Sync frequency range: 30 - 82KHz; Input Video Vertical Sync (frame rate) frequency range: 50-75Hz
Power	External DC - Optional power brick (sold separately) Monitor input power connector: Coaxial power jack (2.0mm (+0.0 -0.1mm) pin outer diameter, 6.4mm (+/- 0.3mm) barrel inner diameter, 8.8mm (+/- 0.3mm) barrel depth); Monitor input power signal specifications: 12VDC +/- 5%; Adapter output power connector: DC barrel plug (2.1mm (+/- 0.1mm) pin inner diameter, 5.5mm (+/- 0.05mm) barrel outer diameter, 9.5mm (+/- 0.3mm) barrel length)
Power Consumption	ON (Default - 75% Brightness): 10.52 W; ON (Typical - 100% Brightness): 11.78 W SLEEP (monitor + power brick): 1.5W OFF (monitor + power brick): 0.5W
Temperature	Operating: 0 °C to 40 °C (32 °F to 104 °F); Storage: -20 °C to 60 °C (-4 °F to 140 °F)
Humidity	Operating: 20% to 80%; Storage: 10% to 95%
Dimensions	Bezel model: 16.33" x 13.50" x 1.97" / 414.7mm x 342.7mm x 50mm Zero-bezel model: 16.54" x 13.70" x 1.60" / 420.1mm x 348.1mm x 40.7mm
Shipping Dimensions	20.71" x 17.72" x 6.85" / 526mm x 450mm x 174mm
Weight	Unpackaged: 10.14 lbs / 4.6 kg; Packaged: 16.31 lbs / 7.4 kg
Mounting Options	100mm VESA mount (zero-bezel models); 75mm and 100mm VESA mount (bezel models) Rear mount (zero-bezel models) 2 Hole mounting interface on all four sides Front mount with optional bezel kit (bezel models see Accessories tab for details) Rack mount with optional kit (bezel models) Flush mount with included brackets (bezel models)
Warranty	3 years standard
MTBF	50,000 hours demonstrated
Agency Approvals	UL, FCC, RCM; cUL, IC; CCC; CE, TUV; VCCI; KCC; CoC; BSMI; CB; EAC; RoHS, China RoHS, WEEE
Compliance	TouchPro PCAP - GLI 27 kV air / 8 kV contact ESD compliant; UL 62368 ball-drop compliant, IK07 impact compliant, IP65 front side
What's in the Box	HDMI Cable, VGA Cable, OSD Remote, Touch USB Cable, Quick Install Guide; For zero-bezel models: Flush Mount Brackets w/Screws; For bezel models: "L" (Side Mount) Brackets w/Screws, EEI Label, Japan Class-B TM info sheet